

# Uninterruptible Power Supply (UPS)

## Powercom UPS King Series



| Model                           |               | KSL-500 AP                                | KIN-1000AP   | KIN-2200AP      | KIN-3000AP      |
|---------------------------------|---------------|---|--|-----------------|-----------------|
| <b>Capacity</b>                 |               | 500VA                                     | 1000VA   | 2200VA          | 3000VA          |
| <b>Input</b>                    | Voltage       | 100V/110V/115V/120V/220V/230V/240V        |  |                 |                 |
|                                 | Voltage Range | +/- 25% Boost and Buck AVR                |  |                 |                 |
|                                 | Frequency     | 50/60Hz +/- 10% (auto sensing)            |  |                 |                 |
| <b>Output</b>                   | Voltage       | 100V/110V/115V/120V/220V/230V/240V +/- 5% |  |                 |                 |
|                                 | Frequency     | 50/60Hz +/- 0.5%                          |  |                 |                 |
|                                 | Waveform      | Simulated sine wave                       |  |                 |                 |
| <b>Transfer Time</b>            |               | ~3ms                                      |  |                 |                 |
| <b>Battery</b>                  | Lifetime      | 3 - 6 years (typical)                     |  |                 |                 |
|                                 | Recharge Time | 4 hours (to 90% of full capacity)         |  |                 |                 |
| <b>Dimensions in mm (WxHxD)</b> |               | 370 x 45 x 330                            | 130 x 201 x 382  | 170 x 225 x 450 | 170 x 225 x 450 |
| <b>Weight in kg</b>             |               | 9.0                                       | 15.0   | 26.2            | 29.8            |
| <b>Environment</b>              | Temperature   | 0 - 40 °C                                 |  |                 |                 |
|                                 | Humidity      | 0 - 95% (non-condensing)                  |  |                 |                 |
| <b>Interface</b>                |               | Smart RS-232                              |  |                 |                 |
| <b>Protection</b>               |               | Overload, Short circuit, Spike protection |  |                 |                 |
| <b>Software</b>                 |               | UPSMON Power Management Software          |  |                 |                 |
| <b>Additional Battery Pack</b>  |               | not available                             | optional (must be purchased with the UPS, cannot be added later) |                 |                 |

- Specifications are subject to change without notice -



RUOSS-KISTLER AG, Kantonsstrasse 55, 8863 Buttikon

Tel.: (+41) 055 464 35 15 Mail: handel@ruoss-kistler.ch  
Fax: (+41) 055 464 35 01 Internet: www.ruoss-kistler.ch